

/ Descriptions

SOT-89 Voltage Regulator in a SOT-89 Plastic Package.


/ Features

100mA,
3-Terminal regulators, output current up to 100 mA, internal thermal overload protection and short-circuit limiting.


/ Applications

Voltage Regulator.

/ / Equivalent Circuit or Application Circuit



/ Pinning




PIN1 OUT PIN 2 GND PIN 3 IN

/ Marking


Marking	HL06
---------	------

Parameter	Symbol	Rating	Unit
-----------	--------	--------	------

/ Package Dimensions



/ Marking Instructions



H

L06

**


Note:

H: Company Code.

L06: Product Type.

**: Lot No. Code, code change with Lot No.

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- 1

150 180

60 90sec;

1.Preheating:150~180 , Time:60~90sec.
- 2

245±5

5±0.5sec;

2.Peak Temp.:245±5 , Duration:5±0.5sec.
- 3

2 10

/sec.

3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	Outer Box
SOT-89	1,000	7	7,000	6	42,000	7 ×12	180×120×180	390×385×205

/ Notices