

5 é / Descriptions

9 5 : . > // x l 9 8 â ' ož
Zener Diode in a SOT-23 Plastic Package.


□^a / Features

S = ô k³ o ` 9 x F v i k ... ` ' +) 7 ö Ö ä U ´ Å } L k —) (D } ož
300mW power dissipation, Ideally Suited for Automated Assembly, Qualified to AEC-Q101 Standards for High Reliability, HF Product.


Đ ÷ / Applications

9 < < ! 8 l 9 è k á V ñ • } Lož
2.4V to 39V wide zener voltage range applications, Meet the stringent requirements of automotive applications.

Ã W] Ô · / Equivalent Circuit



• Ů - æ / Pinning



PIN: See Equivalent Circuit.

, M V / Marking

• Å @ fož See Electrical Characteristics.

@ f	... Z	f >	% y
Parameter	Symbol	Rating	Unit




Electrical Characteristics(Ta=25 ;)

Type Number	Marking Code	Zener Voltage Range (Note 2)				Maximum Zener Impedance (Note 3)			Maximum Reverse Current	
		V _Z @I _{ZT}			I _{ZT}	Z _{ZT} @I _{ZT}	Z _{ZK} @I _{ZK}	I _{ZK}	I _R	@V _R
		Nom (V)	Min (V)	Max (V)	mA			mA	uA	V
BRBZX84B12Q	Q2U	12	11.76	12.24	5	23	141	1	0.09	8
BRBZX84B13Q	Q3U	13	12.74	13.26	5	28	160	1	0.045	8
BRBZX84B15Q	Q4U	15	14.70	15.30	5	28	188	1	0.045	10.5
BRBZX84B16Q	Q5U	16	15.68	16.32	5	37	188	1	0.045	11.2
BRBZX84B18Q	Q6U	18	17.64	18.36	5	42	212	1	0.045	12.6
BRBZX84B20Q	Q7U	20	19.60	20.40	5	51	212	1	0.045	14.0
BRBZX84B22Q	Q8U	22	21.56	22.44	5	51	235	1	0.045	15.4
BRBZX84B24Q	Q9U	24	23.52	24.48	5	65	235	1	0.045	16.8
BRBZX84B27Q	QAU	27	26.46	27.54	5	75	282	0.5	0.045	18.9
BRBZX84B30Q	QBU	30	29.40	30.60	5	75	282	0.5	0.045	21.0
BRBZX84B33Q	CUQ	33	32.34	33.66	5	75	306	0.5	0.045	23.0
BRBZX84B36Q	DUQ	36	35.28	36.72	5	84	329	0.5	0.045	25.2
BRBZX84B39Q	QEU	39	38.22	39.78	5	122	329	0.5	0.045	27.3

Notes:

1. Device mounted on FR-4 PC board with recommended pad layout.
2. Short duration test pulse used to minimize self-heating effect.
3. f = 1KHz.
4. Valid provided the terminals are kept at ambient temperature.

Electrical Characteristic Curve



BRBZX84BXXXQ
Rev.A Jan.-2023



DATA SHEET

5 6.56 735.92 47tp://-5.4 -18.0G718.0()

, M y f / Marking Instructions



^a ¢ y

7 y V ñ —) í D } ö œ

(< y ° Z W A

Note:

Q: Automobile halogen-free product Code

BV: Product Type

BRBZX84BXXXQ
Rev.A Jan.-2023