

BRCL4070ZR-4.2	1.2A	/	BRCL4070ZR-4.2
P-MOSFET			
4.2V		4.2V	1/10

BRCL4070ZR-4.2


6.8V OVP
36V

0V
1.2A
/ /


2.8V

DFN3×3B-8L
RoHS

XVE



/ Pinning



PIN Num.	Symbol	Function
1	TEMP	
2	SUR J	
3	GND	
4	VDD	8Y
5	BAT	
6	STDBY	
7	CHRG	
8	CE	
EPAD	GND	

/ Absolute Maximum Ratings(Ta=25)

PARAMETER	SYMBOL	RATINGS	UNITS
VDD/CHRG/STDBY Pin Voltage	V _{VDD/CHRG/STDBY}	-0.3~30	V
VCE Pin Voltage	V _{CE}	-0.3~36	
BAT Pin Voltage	V _{BAT}	-5~15	
PROG Pin Voltage	V _{PROG}	-0.3~6	
TEMP Pin Voltage	V _{TEMP}	-0.3~25	
Operating Ambient Temperature Range	T _{OP}	-40~+85	°C
Storage Temperature	T _{stg}	-55~+150	°C
Lead Temperature (Soldering, 10s)	T _{solder}	260	°C
ESD	HBM	2000	V
	MM	200	V



PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Power Supply						
Input Supply Voltage	V _{DD}		4.5	5.0	6.0	V
V _{DD} Under Voltage Lockout Threshold	V _{DD_UV}	V _{DD} from Low to High		3.8		V
V _{DD} Under voltage Lockout Hysteresis	V _{DD_UV_HYS}	V _{DD} from High to Low		200		mV
Input Over-Voltage Protection Voltage	V _{DD_OVP}		6.3	6.8	7.3	V
Input Over-Voltage Protection Voltage Hysteresis	V _{DD_OVP_HYS}			500		mV
Input Power Supply Current	I _{CC}	Charging mode (R _{PROG} =1K)		240	360	μA
		Standby mode, charging terminated		70	120	μA
		Shutdown mode (R _{PROG} not connected, V _{CC} <V _{BAT})		50	100	μA
Charging Current Setting						
R _{PROG} voltage at Constant Current Mode	V _{PROG}	V _{DD} =5V;R _{PROG} =1K	0.85	1	1.15	V


BAT Pin Current

I

/ Electrical Characteristics(Ta=25)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Indicator Pin Status CHRG/STDBY						
CHRG Pin Output Current	I _{CHRG}	V _{DD} =5V;V _{CHRG} =1V	1	2.5	5	mA
STDBY Pin Output Current	I _{STDBY}	V _{DD} =5V;V _{STDBY} =1V	1	2.5	5	mA
Internal Temperature Compensation						
Internal Temperature Compensation	T _{OTC}			140		
Overtemperature Detection Threshold	T _{OTPH}	WH P S QWF	43%* VDD	45%* VDD		V
Low Temperature Detection Threshold	T _{OTPL}	WH P S QWF		80%* VDD	82%* VDD	V

/ Principle block diagram



BRCL4070ZR-4.2 /
BRCL4070ZR-4.2 USB AC1.2A ,
6.8V

UVLO PROG 1%
BAT 2.8V,
1/5
BAT 2.8V
BAT BRCL4070ZR-4.2
1/10

$I_{CH} = 1950 / R_{PROG}$ I_{CH}
 R_{PROG} R_{PROG} 200mA
 $R_{PROG} = 1950 / 0.2 = 5.25K\Omega$
 R_{PROG} 1%

R_{PROG}		I_{CH}	
$R_{PROG}(K)$		$I_{CH}(mA)$	
1		1950	
1.2		875	
5		205	
10		100	

BAT 4.05V 2ms $T_{RECHARGE}$
80

/ Function description

140BRCL4070ZR-4.2

UVLOVDDVDD
VDD200mV

BRCL4070ZR-4.2VDD
VDD


BRCL4070ZR-4.2CHRG STDBY
CHRGSTDBYCHRG STDBY

	CHRG/	STDBY/
+WHPS ,		
YGG		

/ Package Dimensions

DFN3X3B-8L

Unit:mm



/ Marking Instructions



EU
7373
XX

BRCL4070ZR-4.2	BR/4070-42/****


() / Temperature Profile for IR Reflow Soldering(Pb-Free)

Note:

- 1 150 180 60 90sec;
 2 245±5 5±0.5sec;
 3 2 10 /sec.

- 1.Preheating:150~180 , Time:60~90sec.
 2.Peak Temp.:245±5 , Duration:5±0.5sec.
 3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units	Dimension	(unit mm ³)
--------------	-------	-----------	-------------------------